




- Visual & Audible Alarm
- 30 Day Replacement Alarm
- Lamp Life Expired Alarm
- UV Lamp Out Alarm
- Internal Resettable Clock with Battery Backup
- Optional Solenoid Added For Fail Safe System





Ultraviolet Series E

SPECIFICATIONS							
Model #	Max. Flow GPM	No. Lamps	KW @ 120V	AMP @ 120V	Pipe Size	Overall Dimensions L x W x D	Shipping Weigh
RWT-8E	8	1	0.035	0.32	3/4" MIP	21" x 5" x 5"	9 Lbs.
RWT-15E	15	1	0.064	0.56	3/4" MIP	21" x 5" x 5"	18 Lbs.



Ultraviolet Disinfection Facts

- 1. U.V. is more effective against viruses than chlorine.
- 2. U.V. is environmentally and user friendly, with no dangerous chemicals to handle or store, no risks of overdosing.
- 3. U.V. is extremely economical, hundreds of gallons may be treated for each penny of operating costs.
- 4. U.V. treatment does not change the taste, odor, pH, or conductivity nor the general chemistry of the water.
- 5. U.V. systems are easy to install with only two water connections and a power cord.
- 6. U.V. systems are compatible with all other water treatment products; R.O. filtration, water conditioning, and softening.
- 7. U.V. systems are easy to maintain with periodic cleaning, and annual lamp replacement.
- 8. U.V. systems operate with no moving parts to wear out, making them one of the most effective and durable water treatment systems on the market.

Solenoid- Optional fail safe shut-off valve. (To be used with U.V. Monitor System)



Distributed By:
Roanoke Water Treatment, Inc.
1948 Franklin Road S.W.
Roanoke, VA 24014
(540)982-2324

